

MORE THAN 25 COLOURS AVAILABLE



\*ACTUAL PRODUCT COLOURS MAY VARY SLIGHTLY FROM THOSE DEPICTED HERE.

APPLICATION PROCESS

- 1 Mix 1kg powder with approximately 0.3 litres (300ml) of water. Mix well until the grout is easily applied with a trowel. Make sure the mixture is not too thin or thick.
- 2 Use a rubber faced grouting trowel or a float to apply the grout mixture evenly between the tiles.
- 3 The grout requires at least 20 minutes to set and dry.
- 4 Remove excess grout from the surface of the tile with a rubber-faced grouting trowel or rubber float using a diagonal motion.
- 5 Let the grout dry thoroughly for around 30 minutes. Then use a damp sponge to gently wipe the surface of the tiles to remove any remaining excess grout (If the surface is rough, clean the surface within 15 minutes).
- 6 Allow at least 24 hours for the grout to harden. Do not wash, trample or step/walk on the surface during this period.
- 7 The proper colour of the grout will show after 48 hours of setting.

TECHNICAL ADVICE

+94 33 4930590



ISO 9001 Certified Company

Manufactured and Distributed by:  
**SWISSTEK (CEYLON) PLC**

No. 215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka.  
Telephone : 011 4526700  
Fax : 011 2805461

FACTORY

No. 330, Belummahara, Imbulgoda.  
Website : [www.swisstekceylon.com](http://www.swisstekceylon.com)

SWISSTEK

TILE GROUT

The Perfect, Professional Finish



The only brand with



POLYMER MODIFIED GROUT

Swisstek Polymer Modified Grout is suitable for both indoor and outdoor applications with high abrasion resistance and reduced water absorption. It also provides excellent bonding strength.



SUPER POLYMER GROUT

Swisstek Super Polymer Modified Grout is suitable for both indoor and outdoor applications with exceptional abrasion resistance, reduced water absorption and excellent bonding strength.

It is highly recommended for swimming pools and its non-sanded, ultra-fine formula is suitable for narrow grooves.



COMPLEMENTARY SWISSTEK PRODUCTS IN GROUTING

Swisstek Lippage Control System

Swisstek Tile Spacers

Swisstek Grout Sealer

SPECIFICATIONS

| Standard Requirement as per ISO 13007-3:2010                     |            | Polymer Modified Grout | Super Polymer Grout |
|--|------------|------------------------|---------------------|
| Shrinkage at 28 days(mm/m)                                       |            | 1.2                    | 1.2                 |
| Flextural Strength after freeze thaw cycle(N/mm <sup>2</sup> )   |            | 6.8                    | 7                   |
| Compressive Strength after freeze thaw cycle(N/mm <sup>2</sup> ) |            | 42.4                   | 34.1                |
| Abrasion Resistance(mm <sup>3</sup> )                            |            | 448                    | 435                 |
| Flextural Strength(N/mm <sup>2</sup> )                           |            | 6.56                   | 6.7                 |
| Compressive Strength(N/mm <sup>2</sup> )                         |            | 31.8                   | 30.4                |
| Water Absorption after   | 30 min(g)  | 1.21                   | 0.35                |
|  | 4 hours(g) | 3.22                   | 0.66                |
| Category   |            | CG2WA                  | CG2WA               |