








# SWISSTEK®

# SILICONE

ALL PURPOSE

THE TRUSTED SEALING SOLUTION

## PRODUCT FEATURES

-  High Tensile Strength
-  Excellent Adhesion
-  No Sag
-  Water Proof
-  Less Odor
-  Non Acidic
-  No Discoloration
-  Capable of  $\pm 25\%$  Joint Movement
-  Resistance for Mold and Yellowing

COLOURS



CLEAR



WHITE



BLACK





## APPLICATION INSTRUCTIONS

- Surfaces must be clean and dry. If cleaning is required, use an OIL -FREE solvent and dry thoroughly.
- Cut nozzle on angle to desired bead size.
- Apply silicone with caulking gun, pushing sealant ahead of nozzle.
- Tooling should be done immediately as sealant will skin in 10 minutes and cure in 24hrs.

## AREA OF APPLICATION

- Bathroom/ Kitchen
- Aluminium doors & windows
- Industrial usage
- Glass & Stone curtain wall
- Exterior & interior decoration

## TECHNICAL DETAILS

Density	1.3 g/ml
Flow/Sag	Nil
Curing rate (23°C/50% RH)	3mm/24 hours
Tensile strength	≥ 2.0 N/mm <sup>2</sup>

## COVERAGE (LINEAR METERS PER 300ML)

WIDTH IN MM		2	3	7	10	12	16	19	25
DEPTH IN MM	2	71.5m	57.0m	20.0m	14.0m	11.5m	8.5m	7.6m	5.5m
	3	-	31.5m	13m	19.5m	7.5m	5.5m	4.5m	3.5m
	5	-	-	8.0m	5.5m	4.5m	3.5m	2.5m	1.5m
	7	-	-	5.5m	3.5m	3.0m	2.0m	1.5m	1.0m

**SHELF LIFE: 15 MONTHS IN SEALED CONDITION AND ROOM TEMPERATURE**



**SWISSTEK (CEYLON) PLC**  
 No. 215, Nawala Road, Narahenpita,  
 Colombo 05, Sri Lanka.  
 Tel: 011 452 6700 Fax: 011 280 5461

**FACTORY** No. 330, Belummahara, Imbulgoda.  
 Website: [www.swisstekceylon.com](http://www.swisstekceylon.com)

 **+94 33 493 0590**