

SWISSTEK GROUT SEALER

FOR THE PERFECT FINISH

TECHNICAL DATA SHEET

Grout sealer is a water based sealer designed for the protection of all sanded and non -sanded grout joint. Grout sealer forms an invisible barrier that is resistant to moisture and stains.



Features

- Water based, ecofriendly sealer
- Economical
- Good permeability, no shine, natural look
- Excellent adhesion and good abrasion resistant
- Good water repellent effect and stain protection
- For interior and exterior use
- Unique applicator tip for easy application

Application scope

For all sanded and non-sanded cementious grout

Application

Surface preparation

SWISSTEK GROUT SEALER





Grout joints must be clean, dry and free from the foreign materials

For newly grouted surfaces, apply the grout sealer after 72 hours of grout application.

For existing old floors; clean the grout surface by using Swisstek heavy dirt tile cleaner. Allow the surface to dry for 24 hours before applying the Swisstek grout sealer.

Apply the sealer using unique applicator tip

If required, second application may be applied within 30 minutes or after ensure the first layer completely absorbed to the surface.

Any grout sealers sitting on an adjoining tile or natural stones must be wiped off with a clean damp towel within few minutes after grout sealer absorbed to the grout joints

The finished area must be kept for 6 hours in its state for curing

For optimum results, the finished area must be kept dry and free from any staining material for 36 hours.

Packing and storage:

200ml/24 bottles in one pack

Store in dry place

Coverage:

400 square feet / bottle

Coverage may be varied depending on the surface porosity, surface absorption and application method.

Shelf Life: 1 year from the date of manufacture

Safety Advices

Keep away from children. /If it comes in contact with the eyes, wash thoroughly

Manufactured and marketed By

Swisstek (Ceylon) PLC (An associate company of Lanka Tiles PLC)

Factory complex, Belummahara, Imbulgoda, SriLanka

Tel: 0334944441/0334944442/0334930590 Fax:0332260406/0335701371

Email: Swisstek@lankatiles.com

