Swissparkett
SOLID WOOD FLOORING

Technical Data Sheet



Product Name	:	**KUKU SOLID FLOORING**
Wood Species	:	Kuku
Scientific Name	:	Pericopsis mooniana
Product Type	:	Solid wood T&G flooring
Size	:	(T) 15 x (W) 90 x (L) 600-1200 mm (T) 18 x (W) 120 x (L) 600-1800 mm
Grade	:	A-One face clear
Moisture Content	:	±8 - 13%
Profile	:	T&G
Finishing	:	Unfinished or UV Coated with Viron UV Lacquer/Unfinished
Colour	:	Rich chocolate brown that darkens with age and often highlighted by lighter streaks Natural color variation between boards is common
Grain/Texture	:	Straight to interlocked grain; medium to coarse texture.
Tree Size	:	30-40 m tall; 0.8-1.2 m trunk diameter
Average Dried Weight	:	800 kg/m^3
Specific Gravity (Basic; 12% MC)	:	0.61; 0.77
Janka Hardness	:	1,700 lbf (7,560 N)
Sustainability	:	Not listed in the CITES Appendices. Harvested in accordance with applicable forestry regulations The species is currently assessed on the IUCN Red List.

Disclaimer: The colours shown are for reference only and may vary from the actual timber colours

SWISSTEK (CEYLON) PLC

Corporate Office: No. 118A, Nawala Road, Narahenpita, Colombo 05
Factory: No. 330, Belummahara, Imbulgoda

Telephone: +94 11 780 7000 I Fax: +94 11 763 4590
Email: info@swisstekceylon.com I Website: www.swisstekceylon.com

SWISSTEK®
FOR THE PERFECT FINISH