Swissparkett
SOLID WOOD FLOORING

Technical Data Sheet



Product Name	:	**TEAK SOLID FLOORING T&G**
Wood Species	:	Teak
Scientific Name	:	Tectona grandis
Product Type	:	Solid wood T&G flooring
Size	:	(T) 18 x (W) 120 x (L) 600 -1800mm
Grade	:	A - One face colour / B
Moisture Content	:	±8 - 13%
Profile	:	T&G
Coloring Agent	:	Maxi Brown LH
Finishing	:	UV Coated with Viron UV Lacquer/Unfinished
Colour	:	Golden or medium brown with age
Grain/Texture	:	Grain is straight, though can occasionally be wavy or interlocked Coarse, uneven texture and moderate to low natural luster
Average Dried Weight	:	630-720 kg/m^3
Specific Gravity (Basic; 12% MC)	:	0.55,0.66
Janka Hardness	:	1,070 lbf (4,740 N)
Sustainability	:	Not listed in the CITES Appendices nor in the IUCN Red List of Threatened Specie

Disclaimer: The colours shown are for reference only and may vary from the actual timber colours

SWISSTEK (CEYLON) PLC

Corporate Office: No. 118A, Nawala Road, Narahenpita, Colombo 05
Factory: No. 330, Belummahara, Imbulgoda

Telephone: +94 11 780 7000 I Fax: +94 11 763 4590
Email: info@swisstekceylon.com I Website: www.swisstekceylon.com

SWISSTEK®
FOR THE PERFECT FINISH